





DT-7524AE2L (D/IR1) Analog Dome Camera



Features

- 1/2.9" 2MP CMOS
- AGC, AWB, BLC, MIR
- Digital WDR/ DNR
- English/Chinese OSD control COC
- AHD / TVI/ CVI / CVBS
- DC12V

Specifications

Image Sensor	1/2 .9" 2MP CMOS
Image Size	1920x1080
Video Output	AHD/TVI/CVI/CVBS
Image System	NTSC (PAL Optional)
Electronic Shutter	Auto;1/50s-1/100000s(PAL);1/60s-1/100000s(NTSC)
IR Distance	10-20m
Frame Rate	30FPS(60Hz), 25FPS(50Hz)
Min. Illumination	0lux (IR On)
Lens	2.8mm
Lens Mount	M12
S/N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP66
Function Control	OSD (COC Control)
Day & Night	ICR
Functions	WDR, DNR, AGC, AWB, BLC, Front Light Compensation, Sharpness, Mirror, Smart IR, Auto Image Setting, Defect Correction, and Angle Adjustment
Languages	Chinese/ English
Power Supply	DC12V (±10%)
Power Consumption	Day: <65 mA; Night: <240 mA
Working Environment	-20°C ~ 50°C, 10% ~ 90% humidity
Dimensions	Ø87mm×108mm

